

# Broadex®

## Sand Filters For Swimming Pools




Quality Management System





- Filter shell made of Laminated Fiberglass Reinforced Polyester.
- Large Transparent Lid of 40 cm diameter including the opening lever, pressure gauge, side mounted multiport valve and air purge.
- Test Pressure 3,5 kg/cm<sup>2</sup>.
- Max operation pressure 2,5 kg/cm<sup>2</sup>.
- Filtration Rate 50 m<sup>3</sup>/h/m<sup>2</sup>



Lid detail

### TECHNICAL CHARACTERISTICS

| MODEL   | BRO-LT 615 | BRO-LT 760 | BRO-LT 920 | BRO-LT 1000 | BRO-LT 1200 |
|---|------------|------------|------------|-------------|-------------|
| D (mm)  | 615        | 760        | 920        | 1000        | 1200        |
| H <sub>1</sub> (mm)   | 820        | 960        | 1110       |             | 1280        |
| H <sub>2</sub> (mm)   | -          | -          | -          |             | -           |
| H <sub>3</sub> (mm)   | 760        | 900        | 1050       |             | 1230        |
| H <sub>4</sub> (mm)   | 260        | 350        | 375        |             | 455         |
| H <sub>5</sub> (mm)   | 410        | 500        | 525        |             | 745         |
| W (mm)  | 260        | 295        | 295        |             | 480         |
| CONNECTIONS Ø (mm)  | 1 1/2"     | 2"         | 2"         |             | 2 1/2"      |
| FLOW (m <sup>3</sup> /h) (50 m <sup>3</sup> /h/m <sup>2</sup> ) | 15         | 22         | 32         |             | 56          |
| SAND (Kg)   | 125        | 250        | 450        |             | 1330        |
| NET WEIGHT (Kg)   | 25,000     | 32,000     | 50,000     |             | 77,000      |



Quality Management System

We reserve the right to change all or part of the features of the articles or contents of this document, without prior notice.

# ERTEK

www.ertek.com

Ertek Yapı ve Makina Endüstri Ekipmanları  
San. ve Tic. Ltd. Şti.

Halkapınar Mah. Pamuk Plaza İş Merkezi 1082  
Sokak No: 3 M 35170 Yenışehir Konak / İZMİR  
Tel: (0232) 469 43 53 Faks: (0232) 457 46 51  
www.ertek.com • info@ertek.com