

Turbidron®

"Turbidron-BL" Bobbin Wound Sand Filters



“Turbidron-BL” Bobbin Wound Sand Filters



- Filter shell made of ABS plastic and reinforced by fiberglass bobbin winding outside.
- Complete with multiport valve.
- Complete with pressure gauge, air purge of 3/8".
- Maximum working pressure 2,5 kg/cm²
- Testing pressure 4,0 kg/cm²
- Filtration rate 50 m³/h/m².



TECHNICAL CHARACTERISTICS

MODEL	TB 450-CL	TB 500-CL	TB 500-BL	TB 630-BL	TB 710-BL	TB 800-BL	TB 900-BL	TB 1000-BL
D (mm)	450	500	500	630	710	800	900	1000
H ₁ (mm)	720	800	760	820	915	975	1020	1410
H ₂ (mm)	630	705	-	-	-	-	-	-
H ₃ (mm)	660	740	700	760	855	915	960	1350
H ₄ (mm)	225	300	305	335	355	375	395	525
H ₅ (mm)	395	440	455	485	515	545	570	685
W (mm)	260	260	260	260	295	295	295	-
CONNECTIONS Ø (mm)	1 1/2"	1 1/2"	1 1/2"	1 1/2"	2"	2"	2"	2 1/2"
FLOW (m ³ /h) (50 m ³ /h/m ²)	8	10	10	14	21	27	32	40
SAND (Kg)	90	100	100	150	250	350	450	700
NET WEIGHT (Kg)	9,200	10,200	17,000	20,000	32,000	38,000	47,000	58,000



We reserve the right to change all or part of the features of the articles or contents of this document, without prior notice.

ERTEK
www.ertek.com

Ertek Yapı ve Makina Endüstri Ekipmanları
San. ve Tic. Ltd. Şti.

Halkapınar Mah. Pamuk Plaza İş Merkezi 1082
Sokak No: 3 M 35170 Yenışehir Konak / İZMİR
Tel: (0232) 469 43 53 Faks: (0232) 457 46 51
www.ertek.com • info@ertek.com

