



GEMAŞ FLAT KOVANSIZ HAVUZ SU ALTI AYDINLATMA LAMBASI MONTAJ TALİMATI

Uyarı: Havuz duvarındaki kablo deliğini gerektiğinde havuz dışından kolaylıkla müdahale edilebilmesi için su hattından 65 cm aşağıda olacak şekilde belirleyiniz.

- 1- İstavrozu fotoğrafta görüldüğü gibi iki vida ile çok sıkmadan ve duvardaki kablo çıkışı merkeze gelecek şekilde yerine sabitleyin




- 2- Lambanın montaj deriniği dikkate alınarak bir kablo sarım uzunluğu belirleyin ve İstavroza fotoğrafta görüldüğü gibi sarın.



Not: İstavroza kolay montajı için kablo sarım bitiş noktasının İstavrozdaki montaj setlerinin altına gelmediğine emin olun



- 3- Lambanın tırnakları ve yuvaları üst üste gelecek şekilde hafif ittirdiğinizde lamba yerine oturacaktır.




- 4- Lambanın çerçevesini vida delikleri ve İstavrozdaki yuvalar üst üste gelecek şekilde yerleştirin ve vidalarıyla yerine sabitleyin.





GEMAŞ FLAT POOL UNDERWATER LIGHT INSTALLATION INSTRUCTION

1- Cross piece is fixed with two pieces screw to the pool as seen on the photo. Cable output on the wall should be on center of cross piece




2- Specify a proper cable according to distance from water line and wind the cable under the cross piece as seen on the photo



Note: Cable winding should not end under the 2 male fixing sets on cross piece.



3- Place the light on the cross piece with housings fit the male fixing sets.



4- Put the frame on the light as the 2 screws holes correspond with screw nests on the fixing sets. Then screw and fix the frame.

